

Package: ordered (via r-universe)

October 7, 2026

Title 'parsnip' Engines and Wrappers for Ordinal Classification Models

Version 0.1.0.9002

Description Bindings, methods, and tuners for using ordinal classification models with the 'parsnip' and 'dials' packages. These include the regularized elastic net ordinal regression of Wurm, Hanlon, and Rathouz (2021) <[doi:10.18637/jss.v099.i06](https://doi.org/10.18637/jss.v099.i06)> in 'ordinalNet', the ordinal classification trees of Galimberti, Soffritti, and Di Maso (2012) <[doi:10.18637/jss.v047.i10](https://doi.org/10.18637/jss.v047.i10)> in 'rpartScore', and the latent variable ordinal forests of Hornung (2020) <[doi:10.1007/s00357-018-9302-x](https://doi.org/10.1007/s00357-018-9302-x)> in 'ordinalForest'.

License MIT + file LICENSE

Depends parsnip (> 1.6.0)

Imports cli, dials (>= 1.4.3), purrr, rlang (>= 1.1.4), tibble, tidyr

Suggests dplyr, MASS, ordinal, ordinalNet, rms (>= 7.0.0), glmnetcr, VGAM, rpartScore, ordinalForest, orf, QSARdata, spelling, testthat (>= 3.0.0)

Remotes tidymodels/parsnip

Config/testthat/edition 3

Encoding UTF-8

Language en-US

Roxygen list(markdown = TRUE)

URL <https://corybrunson.github.io/ordered/>

BugReports <https://github.com/corybrunson/ordered/issues>

Config/Needs/website rmarkdown

Config/roxygen2/version 8.0.0

Config/pak/sysreqs libicu-dev

Repository <https://corybrunson.r-universe.dev>

Date/Publication 2026-09-07 01:11:24 UTC

RemoteUrl <https://github.com/corybrunson/ordered>

RemoteRef HEAD
RemoteSha cc85b9254d8474c617a9df639dcb04d933470762

Contents

clm_parameters	2
ordinalForest_parameters	3
orf_parameters	4
rpartScore_parameters	6
Index	7

clm_parameters	<i>Dials for ordinal engine parameters</i>
----------------	--

Description

The threshold_structure dial is auxiliary to ordinal regression models that use the "clm" engine. It corresponds to the threshold tuning parameter that would be specified using set_engine("clm", ...).

Usage

```
threshold_structure(  
  values = c("flexible", "symmetric", "symmetric2", "equidistant")  
)  
  
values_ordinal_link_clm
```

Arguments

values A character string of possible values.

Details

The vector values_ordinal_link_clm extends the default ordinal_link options encoded in [dials::values_ordinal_link](#) to those accepted by [ordinal::clm\(\)](#).
threshold_structure() is a dial for the threshold structure in cumulative link models. See ?ordinal::clm for more details. Use set_args(threshold = ...) to set this parameter on a model spec. These parameters are engine-specific, not general to ordinal regression models, so are provided here rather than in dials.

Value

An object of S3 parent class param and primary class qual_param; see [dials::new_qual_param\(\)](#).

Examples

```
values_ordinal_link_clm
dials::ordinal_link(values = values_ordinal_link_clm)
threshold_structure()
```

ordinalForest_parameters

Dials for ordinalForest engine parameters

Description

These parameters are auxiliary to random forest models that use the "ordinalForest" engine. They correspond to tuning parameters that would be specified using `set_engine("ordinalForest", ...)`.

Usage

```
naive_scores(values = c(FALSE, TRUE))

num_scores(range = c(100L, 2000L), trans = NULL)

num_score_perms(range = c(100L, 500L), trans = NULL)

num_score_trees(range = c(10L, 200L), trans = NULL)

num_scores_best(range = c(2L, 20L), trans = NULL)

ord_metric(values = values_ord_metric)

values_ord_metric
```

Arguments

values	A character string of possible values.
range	A two-element vector holding the <i>defaults</i> for the smallest and largest possible values, respectively. If a transformation is specified, these values should be in the <i>transformed units</i> .
trans	A trans object from the scales package, such as <code>scales::transform_log10()</code> or <code>scales::transform_reciprocal()</code> . If not provided, the default is used which matches the units used in range. If no transformation, NULL.

Details

The vector `values_ord_metric` provides options to the `ord_metric` dial.

These functions generate parameters for `parsnip::rand_forest()` models using the "ordinalForest" engine. See `?ordinalForest::ordfor()` for more details on the original parameters. These parameters are engine-specific, not general to decision tree models, so are provided here rather than in dials.

- `naive_scores()`: Whether to construct only a "naive" ordinal forest using the scores 1, 2, 3, ... for the ordinal values; tunes `naive`.
- `num_scores()`: The number of score sets tried prior to optimization; tunes `nsets`.
- `num_score_perms()`: The number of permutations of the class width ordering to try for each score set tried (after the first); tunes `npermtrial`.
- `num_score_trees()`: The number of trees in the score set-specific forests; tunes `ntreeperdiv`.
- `num_scores_best()`: The number of top-performing score sets used to calculate the optimized score set; tunes `nbest`.
- `ord_metric()`: The performance function used to evaluate score set-specific forests; tunes `perffunction`. See also `?ordinalForest::perff`.

Value

An object of S3 parent class `param` and primary class `qual_param` or `quant_param`; see `dials::new_qual_param()` and `[dials::new_quant_param()]`.

See Also

`dials::trees()`

Examples

```
naive_scores()
num_scores()
num_score_perms()
num_score_trees()
num_scores_best()
values_ord_metric
ord_metric()
```

orf_parameters

Dials for orf engine parameters

Description

These parameters are auxiliary to random forest models that use the "orf" engine. They correspond to tuning parameters that would be specified using `set_engine("orf", ...)`.

Usage

```
sample_fraction(range = c(0.1, 1), trans = NULL)

honesty(values = c(TRUE, FALSE))

honesty_fraction(range = c(0.1, 0.9), trans = NULL)
```

Arguments

range	A two-element vector holding the <i>defaults</i> for the smallest and largest possible values, respectively. If a transformation is specified, these values should be in the <i>transformed units</i> .
trans	A trans object from the scales package, such as <code>scales::transform_log10()</code> or <code>scales::transform_reciprocal()</code> . If not provided, the default is used which matches the units used in range. If no transformation, NULL.
values	A logical vector of possible values. See <code>values_ord_metric</code> .

Details

These functions generate parameters for `parsnip::rand_forest()` models using the "orf" engine. See `?orf::orf()` for more details on the original parameters. These parameters are engine-specific, not general to random forest models, so are provided here rather than in `dials`.

- `sample_fraction()`: The fraction of observations to be subsampled; tunes `sample.fraction`.
- `honesty()`: Whether to use honest splitting (sample splitting); tunes `honesty`.
- `honesty_fraction()`: The fraction of observations reserved for the honest (estimation) sample; tunes `honesty.fraction`.

Value

An object of S3 parent class `param` and primary class `qual_param` or `quant_param`; see `dials::new_qual_param()` and `dials::new_quant_param()`.

See Also

`dials::trees()`

Examples

```
sample_fraction()
honesty()
honesty_fraction()
```

rpartScore_parameters *Dials for rpartScore engine parameters*

Description

These parameters are auxiliary to decision tree models that use the "rpartScore" engine. They correspond to tuning parameters that would be specified using `set_engine("rpartScore", ...)`.

Usage

```
split_func(values = c("abs", "quad"))  
  
prune_func(values = c("mr", "mc"))
```

Arguments

values A character string of possible values.

Details

`split_func` and `prune_func` are dials for `split` and `prune`, respectively. See `?rpartScore::rpartScore` for more details on the original parameters. These parameters are engine-specific, not general to decision tree models, so are provided here rather than in `dials`.

Value

An object of S3 parent class `param` and primary class `qual_param`; see `dials::new_qual_param()`.

See Also

[dials::trees\(\)](#)

Examples

```
split_func()  
prune_func()
```

Index

`clm_parameters`, 2

`dials::new_qual_param()`, 2, 4–6
`dials::new_quant_param()`, 5
`dials::trees()`, 4–6
`dials::values_ordinal_link`, 2

`honesty (orf_parameters)`, 4
`honesty_fraction (orf_parameters)`, 4

`naive_scores`
 `(ordinalForest_parameters)`, 3
`num_score_perms`
 `(ordinalForest_parameters)`, 3
`num_score_trees`
 `(ordinalForest_parameters)`, 3
`num_scores (ordinalForest_parameters)`, 3
`num_scores_best`
 `(ordinalForest_parameters)`, 3

`ord_metric (ordinalForest_parameters)`, 3
`ordinal::clm()`, 2
`ordinalForest_parameters`, 3
`orf_parameters`, 4

`parsnip::rand_forest()`, 4, 5
`prune_func (rpartScore_parameters)`, 6

`rpartScore_parameters`, 6

`sample_fraction (orf_parameters)`, 4
`split_func (rpartScore_parameters)`, 6

`threshold_structure (clm_parameters)`, 2

`values_ord_metric`
 `(ordinalForest_parameters)`, 3
`values_ordinal_link_clm`
 `(clm_parameters)`, 2